

Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600226

· Trade name: Construction Power Adhesive E-COLL

· Article number: 4317784298919

· UFI: 1U15-FVNJ-A80X-CNWH

1.2 Relevant identified uses of the substance or mixture and uses advised against

#### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal

Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

## **SECTION 2: Hazards identification**

#### · 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

## · 2.2 Label elements

### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 1)

### · Hazard pictograms





GHS07 GHS08

## · Signal word Danger

#### · Hazard-determining components of labelling:

4,4'-Methylenediphenyldiisocyanate, oligimers

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, polymer with 1,2-ethanediamine, methyloxirane and oxirane

#### · Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

## · Additional information:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

EUH204 Contains isocyanates. May produce an allergic reaction.

EUH208 Contains 4,4'-Methylenediphenyldiisocyanate, oligimers, Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, polymer with 1,2-ethanediamine, methyloxirane and oxirane. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 2)

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 25686-28-6	4,4'-Methylenediphenyldiisocyanate, oligimers  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
	Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, polymer with 1,2-ethanediamine, methyloxirane and oxirane Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH208	25-50%
CAS: 9016-87-9 Reg.nr.: 01-2119457024-46-xxxx	diphenylmethanediisocyanate,isomeres and homologues  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335  EUH204  Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %  Skin Irrit. 2; H315: C ≥ 5 %  Resp. Sens. 1; H334: C ≥ 0.1 %  STOT SE 3; H335: C ≥ 5 %	10-50%
CAS: 6425-39-4 EINECS: 229-194-7	2,2'-dimorpholinyldiethyl ether Skin Irrit. 2, H315; Eye Irrit. 2, H319	<2.5%
CAS: 68479-98-1 EINECS: 270-877-4 Index number: 612-130-00-0	diethylmethylbenzenediamine  STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319	<1.25%
CAS: 5873-54-1 EINECS: 227-534-9 Index number: 615-005-00-9 Reg.nr.: 01-2119480143-45xxxx	o-(p-isocyanatobenzyl)phenyl isocyanate  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335  EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	<1.25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 4)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 3)

#### · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

# · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Printing date 21.02.2022 Version

Version number 305 (replaces version 304)

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 4)

Revision: 21.02.2022

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Provide floor trough without outlet.
- $\cdot$  Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: -
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

### · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2

(Contd. on page 6)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 5)

### · Hand protection



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.

## · Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

- $\cdot$  9.1 Information on basic physical and chemical properties
- · General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Colourless
 Characteristic
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: > 193 °C
Ignition temperature: >500 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

• Dynamic: Not determined.

Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

Density and/or relative density

Density at 20 °C:
 Relative density
 1.12 g/cm<sup>3</sup>
 Not determined.

(Contd. on page 7)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Not determined.

**Trade name: Construction Power Adhesive E-COLL** 

(Contd. of page 6)

· Vapour density

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

• Organic solvents: 0.0 % • VOC (EC) % 0,00 %

· VOC (EC) g/l

· VOCV (CH) 0 % 0,00 %

Change in condition

· Softening point/range

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.

(Contd. on page 8)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 7)

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

	· LD/LC50 values relevant for classification:				
İ	CAS: 64	125-39	-4 2,2'-dimorpholinyldiethyl ether		
Ì	Oral	LD50	2,020 mg/kg (rat)		
	Dermal	LD50	3,030 mg/kg (rabbit)		
İ	CAS: 68479-98-1 diethylmethylbenzenediamine				
İ	Oral	LD50	738 mg/kg (rat)		
	Dermal	LD50	>2,000 mg/kg (rat)		

#### · Skin corrosion/irritation

Causes skin irritation.

## · Serious eye damage/irritation

Causes serious eye irritation.

## · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

#### · Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.

## · STOT-single exposure

May cause respiratory irritation.

#### · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

## · Endocrine disrupting properties

None of the ingredients is listed.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 8)

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Very toxic for aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

Also poisonous for fish and plankton in water bodies.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

# · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

## **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR UN-· ADN, IMDG, IATA Void

(Contd. on page 10)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA

ClassLabelADN/R Class:Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· Hazard identification number (Kemler code): -

14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

· UN "Model Regulation": UN-, -

### **SECTION 15: Regulatory information**

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56b, 74
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.
- EUH208 Contains \$. May produce an allergic reaction.

(Contd. on page 11)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: Construction Power Adhesive E-COLL

(Contd. of page 10)

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

Date of previous version: 21.02.2022
Version number of previous version: 304

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the previous version altered.