

Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600191

· Trade name: Gun-applied foam E-COLL

· Article number: 4317784150910

· UFI: GSUQ-FYV6-J80Q-UV6R

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues propane dimethyl ether

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

r 101 I i i i i i i i i i i advice is needed, nave product container of label at hand	P101	If medical advice is needed, have product container or label at hand.
---	------	---

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

2001 pto 11 minute of cubetaness notes a seed a seed and the manufacture additioned.					
· Dangerous components:					
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	25-50%			
Reg.nr.: 01-2119457024-46-xxxx	 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 				
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %				
	Škin Irrit. 2; H315: C ≥ 5 %				
	Resp. Sens. 1; H334: C ≥ 0.1 %				
	STOT SE 3; H335: C ≥ 5 %				
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	10- <25%			
Reg.nr.: 01-2119447716-31-xxxx					
CAS: 74-98-6	propane	2.5-10%			
EINECS: 200-827-9	Flam. Gas 1A, H220				
Index number: 601-003-00-5	Acute Tox. 1, H330				
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas (Comp.), H280				
CAS: 75-28-5	isobutane	2.5-10%			
EINECS: 200-857-2	Flam. Gas 1A, H220				
Index number: 601-004-00-0	Press. Gas (Comp.), H280				
Reg.nr.: 01-2119485395-27-xxxx		0.5.400/			
CAS: 115-10-6	dimethyl ether	2.5-10%			
EINECS: 204-065-8 Index number: 603-019-00-8	♦ Flam. Gas 1A, H220♦ Acute Tox. 2, H330				
Reg.nr.: 01-2119472128-37-xxxx					
1169.111 01-2119472120-37-XXXX	1 1633. Oda (Odilip.), 1 1200				

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 3)

· After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Mouth respiratory protective device.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

 Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

· DNELs

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

Dermal Long term value for employees 0.528 mg/kg bw/Tag Inhalative Long term value for employees 0.93 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 6)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 5)

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A/P2

· Hand protection



Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Different according to colouring

· Odour: Characteristic · Odour threshold: Not determined.

· Boiling point or initial boiling point and boiling

Undetermined. Melting point/freezing point:

range

Not applicable, as aerosol. Not applicable. Flammability

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined.

Not applicable, as aerosol. · Flash point:

· Ignition temperature: 235 °C

· Decomposition temperature: Not determined.

(Contd. on page 7)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 6)

· pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

• Dynamic: Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 5.200 hPa

· Density and/or relative density

Density at 20 °C: 0.9 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent separation test:

· Organic solvents: 24.0 %

· VOC (EC) g/l

- Solids content: 30.0 %

Change in conditionSoftening point/range

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

· Aerosols

Extremely flammable aerosol. Pressurised container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 7)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:			
CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues			
Oral	LD50	10,000 mg/kg (rat) (Literatur)	
Dermal	LD50	>5,000 mg/kg (rabbit) (Literatur)	
		11 mg/m³ (rat)	
CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate			
Oral	LD50	3,600 mg/kg (rat)	
CAS: 74-98-6 propane			
Inhalative	LC50/4h	>20 mg/m³ (rat)	
CAS: 115-10-6 dimethyl ether			
Inhalative	LC50/4h	308 ppm (rat)	

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 8)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

(Contd. on page 10)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 9)

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2 Gases. · Label 2.1

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

- EU ---



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 10)

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220	Extremely	/ flammable	าดลร
11220			

Contains gas under pressure; may explode if heated. H280

Harmful if swallowed. H302

Causes skin irritation. H315

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

Harmful if inhaled. H332

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: Product safety department

 Contact: Head of Product Safety Department · Date of previous version: 21.02.2022

· Version number of previous version: 303

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: Gun-applied foam E-COLL

(Contd. of page 11)

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

· * Data compared to the previous version altered.