Revision: 21.02.2022



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.02.2022

Version number 304 (replaces version 303)

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600185

· Trade name: ECO Montageschaum E-COLL

· Article number: 4317784524797

· UFI: CAXJ-K341-VA06-YNTH

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 1)

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  Flam. Gas 1A, H220 Acute Tox. 2, H330 Press. Gas (Comp.), H280	10- <25%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Tress. Gas 1A, H220  Press. Gas (Comp.), H280	10- <25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280	10- <25%
CAS: 6425-39-4 EINECS: 229-194-7	2,2'-dimorpholinyldiethyl ether  Skin Irrit. 2, H315; Eye Irrit. 2, H319	<2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

## · 4.1 Description of first aid measures

#### · General information:

Personal protection for the First Aider.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 2)

Immediately remove any clothing soiled by the product.

#### · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

#### · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Pick up mechanically.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Open and handle receptacle with care. Store in cool, dry place in tightly closed receptacles. Use only in well ventilated areas.

### · Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

## · 7.2 Conditions for safe storage, including any incompatibilities

### · Storage:

## · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

#### · Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

### · Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 5)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 4)

#### · Additional information:

The lists valid during the making were used as basis.

The usual precautionary measures when handling chemicals must be observed. do not eat and drink during work. Do not smoke while working. Wash hands before breaks and at the end of work.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment

#### · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

#### · Respiratory protection:

The selection of respiratory protection masks (EN 14387) must be based on the known or expected concentrations, the dangers of the product and the occupational exposure limit values (Section 8.1) of the respective respiratory protection mask.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

#### · Hand protection



Protective gloves

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · For the permanent contact gloves made of the following materials are suitable:

Viton

Recommended thickness of the material: ≥ 0.4 mm

Penetration time (min.): >30 min.

#### · As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.1 mm

- · Eye/face protection Recommendation: safety glasses with side protection shield
- · Body protection: Light weight protective clothing

#### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour:

Colourless

· Odour:

Characteristic

· Odour threshold:

Not determined.



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 5)

Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: Not applicable, as aerosol.

Ignition temperature: 235 °C

Decomposition temperature:
 pH
 Not determined.
 Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 5,200 hPa

· Density and/or relative density

Density at 20 °C: 0.92 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent separation test:

· Organic solvents: 22.0 %

· VOC (EC) g/I

· VOCV (CH) 33.00 %

· Change in condition

· Softening point/range

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

· Aerosols

Extremely flammable aerosol. Pressurised container: May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids

(Contd. on page 7)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

Self-heating substances and mixtures     Substances and mixtures, which emit flamma	Void I <b>ble</b>	(Contd. of page 6)
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
   No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 7)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue		
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
15 01 04	metallic packaging	

### **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR UN1950 AEROSOLS

(Contd. on page 9)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 8)

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2 Gases.

· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

#### **SECTION 15: Regulatory information**

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I

Methanol

None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 10)



Printing date 21.02.2022 Version number 304 (replaces version 303) Revision: 21.02.2022

Trade name: ECO Montageschaum E-COLL

(Contd. of page 9)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

#### Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

 Date of previous version: 21.02.2022 · Version number of previous version: 303

## · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 2: Acute toxicity - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· \* Data compared to the previous version altered.